

elite



EASY IP DOME CAMERA


- ✓ 4 Megapixel Image Quality
- ✓ 30m Nightvision Range
- ✓ 2.8mm Fixed Wide Angle Lens
- ✓ IP67 Weatherproof
- ✓ Available in Grey & White
- ✓ Ultra H.265 Video Compression
- ✓ ONVIF Compatible

COMPATIBLE ACCESSORIES


RING BASE
M1P-DB3A1-E



INTERNAL WALL MOUNT
M1P-B3AWM1-E



EXTERNAL WALL MOUNT
M1P-B3AWM2-E



POLE MOUNT
M1P-APM03



TECHNICAL SPECIFICATIONS

M1P-C3A40F-E

CAMERA

Sensor	1/3", 4.0 megapixel, progressive scan, CMOS
Lens	2.8mm@F2.0
Angle of View (H/V/O)	104.4° / 39.6° / 97.0°
Shutter	Auto/Manual, 1/6~1/100000 s
Minimum Illumination	Colour: 0.02 Lux (F2.0, AGC ON), 0 Lux with IR on
Digital Noise Reduction	2D/3D
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>52dB
IR Range	Up to 30m (98 ft) IR range
WDR	DWDR

VIDEO

Video Compression	Ultra 265,H.265, H.264, MJPEG
H.264 Code Profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main Stream:4MP (2592*1520): Max. 20 fps; Sub Stream:720P (1280*720): Max. 30 fps; Third Stream:D1 (720*576): Max. 30 fps
OSD	Up to 4 OSDs
Privacy Mask	Up to 8 Areas
ROI	Up to 2 Areas
Motion Detection	Up to 4 Areas

NETWORK

Supported Protocols	IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP, RTP,RTSP,RTCP,DNS,DDNS,NTP,FTP,UPnP,HTTP,HTTPS,SMTP, SSL
Compatible Integration	ONVIF(Profile S), API

INTERFACE

Network	10/100M Base-TX Ethernet
---------	--------------------------

GENERAL

Power Supply	12 V DC±25%, PoE (IEEE802.3 af), Power consumption: Max 5.5W
Working Environment	-30°C ~ +60°C (-22°F ~ 140°F), Humidity :10%~90% RH
Ingress Protection	IP67
Dimensions (Ø x H)	Φ118x 96 mm (Φ4.6" x 3.8")
Weight (without HDD)	0.33Kg